

ASPECTS OF USE OF CFD FOR UAV CONFIGURATION DESIGN

Presentation at UAV Workshop,
Bath University, November 2002

Tim Pemberton,
Senior Specialist, BAE SYSTEMS

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 26 JUL 2004		2. REPORT TYPE N/A		3. DATES COVERED -	
4. TITLE AND SUBTITLE Aspects Of Use Of Cfd For Uav Configuration Design				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) BAE SYSTEMS				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited					
13. SUPPLEMENTARY NOTES See also ADM001685, CSP 02-5078, Proceedings for Aerodynamic Issues of Unmanned Air Vehicles (UAV)., The original document contains color images.					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UU	18. NUMBER OF PAGES 20	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

UCAV DESIGN PROBLEM

- Problem (for Aerodynamics) is as much due to novel planforms as Unmanned
- Novel planforms negate traditional Aerodynamic ground rules (sweep, span, AR etc)
- S&C is a significant challenge
- Requirement for rapid proto-typing for planform/basic layout studies and control surface optimisation
- Fast-response WT - small scale, stereo-lithography, PSP
- Fast-response CFD -Euler, High RE turb models RANS


TYPICAL EXAMPLE

Investigation of Fin Position on a typical Novel Planform



- Establish credibility of CFD for prediction of general flow trends at low speed, high incidence for novel planforms
- Assist in interpretation of 'small-scale' wind tunnel testing

TYPICAL EXAMPLE

BAE SYSTEMS



Small Scale WT testing -
Effect of fin position



Datum (flat-plate) model


NOTES ON CFD CALCULATIONS

- 6-8million unstructured grid cells required for credible vortex capture from Euler, with particular emphasis on field resolution
- 2-3million 'BAE Systems Autogrid' cells required for equivalent capture from RANS
- $k\epsilon$ RNG turbulence model (wall function) suitable
- Euler solution turnaround 4hrs on 8 Origin processors, RANS 2 days


EFFECT OF FIN POSITION

BAE SYSTEMS





Datum



Fin Pos2







Fin Off

Moderate
IncidenceHigh
Incidence

Flat Plate CFD Euler, local velocity contours

EFFECT OF FIN ON FORCES







BAE SYSTEMS



Flat Plate Wind Tunnel v CFD (Euler)

EFFECT OF FIN ON FLOWFIELD

BAE SYSTEMS



High Inc

Datum


Fin Pos2

Fin Off


Flat Plate CFD Euler, velocity vectors, local vel contours

INVISCID v VISCOUS

BAE SYSTEMS



EULER



RANS





High Inc

Flat Plate CFD Euler v RANS

EFFECT OF THICKNESS

BAE SYSTEMS


Flat Plate

10% t/c Moderate
IncidenceHigh
Incidence


Flat Plate v Symmetric airfoil, CFD Euler, local vel contours

EFFECT OF THICKNESS (FIN OFF) BAE SYSTEMS


10% t/c






5% t/c



Flat Plate



Moderate
incidence









High
Incidence

Flat Plate v Symmetric airfoil, CFD Euler, local vel contours

EFFECT OF T/C ON FLOWFIELD

BAE SYSTEMS



High Inc

10% t/c

5% t/c

Flat plate

CFD Euler, velocity vectors and local vel contours




EFFECT OF T/C, EULER v RANS

BAE SYSTEMS

10% t/c




5% t/c

Flat Plate



Euler

High Inc




RANS

Flat Plate v Symmetric airfoil, Euler v RANS

EFFECT OF THICKNESS

BAE SYSTEMS

10% t/c



5% t/c



Flat Plate



High Inc

RANS

CFD RANS, surface flow patterns

SUMMARY

- Euler showing good prediction of flat plate
- Absolute values of pitching moment poor at high incidence, though engineering decisions can be made by interpretation
- RANS improves absolute predictions, though at too great an overhead in CPU time to be practical for design optimisation
- Difference in flow behaviour between thin and thick airfoils defines limit of applicability of flat plate wind tunnel models


FURTHER ASSESSMENT OF CFD

- RANS assessed on BAE Systems Autogrid meshes for a vortical flow case and a mixed attached/separated flow case
- kg results poor for both cases in terms of comparison with limited WT data, RANS ($k\epsilon$ RNG) and engineering judgement
- $k\epsilon$ RNG results good for both cases

VORTICAL FLOW CASE

BAE SYSTEMS

EULER




RANS

MIXED ATTACHED/SEPARATED FLOW CASE

BAE SYSTEMS


BWB




MIXED ATTACHED/SEPARATED FLOW CASE

BAE SYSTEMS

BWB High Incidence



RANS KERNG



WIND TUNNEL

CONCLUSIONS

- Novel Planforms mean S+C Issues must be addressed early in the UCAV design cycle
- CFD and WT must work together here
- Requirement for rapid assessment
- Flat-plate and stereo-lith small-scale WT models, in conjunction with Euler and 'reduced-accuracy' RANS CFD can be applied here
- This approach requires engineering judgement and expertise to be fully effective